



- 10) CRIMPING WIRE TENSILE FORCE IS BASE ON COPPER BREAK OFF INTENSITY.
- 9) TEMPERATURE RANGE -40°C TO +120°C.
- 8) VOLTAGE-MAX [VOLTS] PER WIRE SPECIFICATION.
- 7) MATCHING WITH TAB to.6 X W2.2.
- 6) TENSILE FORCE : MIN 0.25KG.
- 5) INSERT FORCE : MAX 0.60KG.
- 4) THICKNESS PLATING MORE THAN 40µ INCH.
- 3) PACKING QTY : 4500 PCS/REEL.
- 2) WIRE INSULATION (O.D) : 2.4MM.
- 1) APPLICABLE WIRE RANGE : 0.85-0.38MM².

SPECIFICATION :

**FOR REFERENCE ONLY**

REV.	DATE	APPLICABLE (2) FV-JC-10F CHANGE TO 090 SERIES AMENDMENT	SHEET OF : 1 / 1	EFFECTIVE DATE : 25/7/08	A1231	(1) 27090S/M/H (2) 090 SERIES
05	25/7/08					
REVISION:			MATERIAL:			
05			to.25 BRASS			
TOLERANCE UNLESS OTHERWISE SPECIFIED:			C2680			
X.XXX +/-0.05			DIMENSIONS : MM			
X.XX +/-0.10			DWN: KS YEW			
X.X +/-0.20			CHK: CHUANG			
X +/-0.50			APVD: CHUANG			
TREATMENT SELECTIVE			PRE TIN PLATED			
PART NAME:			17090H-2T			
090 SERIES FEMALE TERMINALS			PART NUMBER			
APPLICABLE (1) TERMINALS (2) HOUSING			Eiamp Precision Industry(M) Sdn.Bhd.			