



- 11) CRIMPING WIRE TENSILE FORCE IS BASE ON COPPER BREAK OFF INTENSITY.
- 10) TEMPERATURE RANGE -40°C TO +120°C.
- 9) VOLTAGE-MAX [VOLTS] PER WIRE SPECIFICATION.
- 8) (17) FOR REFERENCE ONLY.
- 7) MATCHING WITH TAB 10.8 X W6.1 OR ATTY FUSE 10.65 X W5.3.
- 6) TENSILE FORCE : MIN 0.50KG.
- 5) INSERT FORCE : MAX 1.80KG.
- 4) THICKNESS PLATING MORE THAN 40µ INCH.
- 3) PACKING QTY : 4000 PCS/REEL.
- 2) WIRE INSULATION (O.D) : 3.5MM.
- 1) APPLICABLE WIRE RANGE : 2.12~0.94MM².

FOR REFERENCE ONLY

SPECIFICATION :

REVISION:

08 15/4/11 (7) ADD ATTY FUSE 10.65 X W5.3

07 3/2/09 (18) FR 1.25+/-0.25 TO 1.35+/-0.25, (24) FR 7.2 TO 6.8, (6) TENSILE FORCE: MIN 0.70KG CHANGE TO MIN 0.50KG.

REV. DATE

AMENDMENT

SHEET OF : 1 / 1

MATERIAL: C2680
 DIMENSIONS : MM
 TOLERANCE UNLESS OTHERWISE SPECIFIED:

X.XXX +/-0.05
 X.XX +/-0.10
 X.X +/-0.20
 X +/-0.50

EFFECTIVE DATE : 15/4/11

| | | | | |
|---|---------------------|------------------------|--------------|-------------------|
| PREPARE BY: KS YEW | REVIEWED BY: CH ANG | APPROVED BY: YL CHUANG | SCALE : FREE | DRAWING NO: A1277 |
| TREATMENT SELECTIVE | PRE-TIN PLATED | TIN PLATING | NONE | |
| PART NUMBER | 172503H-2T | 172503H-2 | 172503H-1 | |
| PREPARE BY: KS YEW | REVIEWED BY: CH ANG | APPROVED BY: YL CHUANG | SCALE : FREE | DRAWING NO: A1277 |
| TREATMENT SELECTIVE | PRE-TIN PLATED | TIN PLATING | NONE | |
| PART NUMBER | 172503H-2T | 172503H-2 | 172503H-1 | |
| PART NAME: 250 SERIES FEMALE TERMINALS APPLICABLE (1) TERMINALS (2) HOUSING (1) 272503S/M/H (2) 250 SERIES HOUSING | | | | |

EBI Terminals & Connectors
 Elamp Precision Industry(M) Sdn.Bhd.